

UFKES
Greentec



PANTHERA

UFKES
Greentec

Greentec
■ **PANTHERA**

FORESTLINE


Greentec PANTHERA



Container chassis (hooklift)



Tracks



Unit motor mounted



3-axle semi-trailer



Standing infeed rollers on both sides of the infeed



Infeedtable with continuously closed infeedchain up to the infeed

- Ufkes direct flow system, chips are directly blown in the heart of the suction blower
- At this position the blowing blades have the lowest speed. The uniform quality woodchip won't be smashed. The chips are directed to the outside of the blower by the centrifugal force where they come out of the chute with high blowing force
- Rest material of the infeedchain and under the drum will be transported to the blower with 3 augers to avoid spillage underneath the machine

Greentec PANTHERA

Infeed opening (mm)	1000 x 2140
Feed opening channel (mm)	900 x 1400
Max. infeed softwood (mm)	Ø 900
Drum (mm)	Ø 1040 x 1400
Standing infeed rollers (mm)	Ø 370 x 1000
Chipper knives	6
Anvil knives	1
Max. chip length (mm)	55 (75)

Equipped with large diameter blower 1500mm, speed easy continuously adjustable on joy-stick from 180 to 400 RPM

Open style knivedrum, 400-500 RPM

Knives are multiple sharpening, with shims easy to fill and adjust. Equipped with obstacle prevention, knives can move to the back

Knives are adjustable and can fold away at calamity

Standard equipped with toolboxlift for easy acces for service on the knivedrum

Automatic reversible fan for cleaning the radiator

GCS 6.0 control (Greentec Control System)




900 x 1400 mm



≤ 90 cm



900 HP



20-55 (75) mm